



 VIDEO TUTORIAL


## Important!

This replacement procedure can be used for:
MERCEDES-BENZ A-CLASS (W169) A 150 (169.031, 169.331), MERCEDES-BENZ A-CLASS (W169) A 160 (169.031, 169.331), MERCEDES-BENZ B-CLASS (W245) B 150 (245.231), MERCEDES-BENZ B-CLASS (W245) B 160 (245.231)

---

The steps may slightly vary depending on the car design.

# REQUIRED TOOLS:




- Wire brush
- WD-40 spray
- Brake cleaner
- Brake caliper guide pins grease
- Copper grease
- Sealant
- Torx bit T30
- Combination spanner #13
- Combination spanner #15
- Combination spanner #16
- Wheel impact socket #17
- Brake caliper wind back tool
- Ratchet wrench
- Torque wrench
- Crow bar
- Wheel chock

## AUTODOC recommends:

- Replace the brake disks on the car Mercedes-Benz W169 in complete set for each axis. Regardless of the state of components. This will ensure even braking.
- The replacement procedure is identical for both brake disks on the same axle.
- When changing the brake discs, always replace the brake pads.
- All work should be done with the engine stopped.

## CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1



Open the bonnet. Unscrew the brake fluid reservoir cap.

2



Secure the wheels with chocks.

3



Loosen the wheel mounting bolts. Use wheel impact socket #17.




Raise the rear of the car and secure on supports.

5



Unscrew the wheel bolts.

## AUTODOC recommends:

- To avoid injury, hold up the wheel when unscrewing the bolts.

6



Remove the wheel.

7

Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.


8




Unscrew the brake caliper fastening. Use a combination spanner #13. Use a combination spanner #15.


9



Spread the brake pads. Use a crowbar.

10



Remove the brake caliper.

## AUTODOC recommends:

- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.

11



Remove the brake pads.

12




Clean the brake caliper bracket fasteners. Use a wire brush. Use WD-40 spray.

13



Unscrew the caliper bracket fastening. Use a combination spanner #16.

14



Remove the caliper bracket



15




Clean the brake disc fasteners. Use a wire brush. Use WD-40 spray.

16



Unscrew the brake disc fastening Use Torx T30. Use a ratchet wrench.

17



Remove the brake disc.

18

Clean the hub. Use a wire brush.

19



Treat the contacting surface. Use copper grease.

20



Move the parking brake shoes against the drum. Use a crowbar.

21




Install the brake disc.

22



Tighten the brake disc fastening. Use Torx T30. Use a torque wrench. Tighten it to 9 Nm torque.

23



Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.

## AUTODOC recommends:

- After applying the spray, wait a few minutes.


24

Remove the guide pins from the brake caliper.

25

Clean old grease and rust stains, if there are any, from the caliper guide pins and guide pin boots.

26



Treat the brake caliper guide pins. Use the brake caliper guide pin grease. Screw in the guide pins.

27

Treat the fastening bolts. Use a sealant.

28



Install the brake caliper bracket

29

Tighten the brake caliper bracket Use a combination spanner #16. Use a torque wrench. Tighten it to 70 Nm torque.

30




Install the brake pads.

31

Treat the brake caliper piston. Use a brake cleaner.

## AUTODOC recommends:


- After applying the spray, wait a few minutes.

32



Press in the brake caliper piston. Use brake caliper wind back tool.

33



Install the brake caliper and fix it. Use a combination spanner #13. Use a combination spanner #15. Use a torque wrench. Tighten it to 35 Nm torque.

34



Treat the surface where the brake disc contacts the wheel rim. Use copper grease.

35



Clean the brake disk surface. Use a brake cleaner.

## AUTODOC recommends:

- After applying the spray, wait a few minutes.

36




Install the wheel.

## AUTODOC recommends:

- To avoid injury, hold up the wheel when screwing in the fastening bolts.

37




Screw in the wheel bolts. Use wheel impact socket #17.

38



Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 120 Nm torque.

39



Remove the jacks and chocks.

## AUTODOC recommends:

- Check the brake fluid level in the expansion tank and refill if necessary.

40



Tighten the brake fluid reservoir cap. Without starting the engine, press the brake pedal several times until you feel significant resistance.



41



Close the hood.

## DID YOU FIND THESE INSTRUCTIONS HELPFUL?

YES


NO




BECOME A MEMBER OF AUTODOC CLUB!

# AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING




A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR



BUY SPARE PARTS FOR MERCEDES-BENZ



BRAKE DISCS: A WIDE SELECTION




CHOOSE CAR PARTS FOR MERCEDES-BENZ W169


BRAKE DISCS FOR MERCEDES-BENZ: BUY NOW






## Disclaimer:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AutoDoc shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AutoDoc shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AutoDoc shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AutoDoc strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.